

**Ref.**

**36540**

Colección / Collection / Collection	Technical Indoor. PRO Professional LED
Descripción / Description / Description	Panel LED LED Panel Panneau LED

**Características Luminaria / Light Data Sheet /  
Caractéristiques de la Luminaire**

Material / Material / Matériau	Aluminio / Aluminium / Aluminium		
Material Difusor / Difusor Material / Matériau Diffuseur	PMMA		
Acabado Difusor / Diffuser Finish/ Touche Finale du Diffuseur	Ácido / Acid / Acide		
Colores / Colours / Couleurs	90 Blanco Técnico / Technical White / Blanc Technique		
Vatios / Watts / Watts	40W		
Lúmens / Lumens / Lumens	Color T. <sup>a</sup>	Useful Lm	Chip Lm
	4000K	4516 lm	4800 lm
Grados Apertura / Opening Angle / Angle d'ouverture	120°		
IP	65		
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	15.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C to +45°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-90% RH		
Peso / Weight / Poids	3,12 Kg		
Cantidad / Pieces / Quantité	1/ 4		

**Características del Chip / Chip Data Sheet /  
Caractéristiques de la Puce**

Marca / Brand / Marque	SANAN
Tipo / Type / Type	SMD 4014
L70 B10	50.000 h
SDCM (Mac Adam)	5
EN62471	RG1
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	120 Lm/W (4000K)

**Características Driver / Driver Data Sheet /  
Caractéristiques de l'Alimentateur**


Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Intensidad de Funcionamiento Working Current Courant de Fonctionnement	Flicker
36540-298_-	ON-OFF. Non Dimmable	AC200-240V 50/60Hz	>0,9	5	1000 mA	Free

Colores / Colours / Couleurs



90 Blanco Técnico / Technical White  
/ Blanc Technique

Accesorios / Accessories / Accessoires



JISO Smart Control



2DCLEDK1



2DCLEDK2



DC31036-2



DC30040-3



DC32440-4



DC6060-4



DC31036-1



DC31640-0

Productos Relacionados / Related Products / Produits Associés



32428



36540



32940



32940



39897

Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

[http://www.jisoiluminacion.es/CE/Empotrables\\_D.pdf](http://www.jisoiluminacion.es/CE/Empotrables_D.pdf)

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

[http://www.jisoiluminacion.es/Instrucciones/365\\_1.pdf](http://www.jisoiluminacion.es/Instrucciones/365_1.pdf)

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

[http://www.jisoiluminacion.es/Ficheros\\_LDT/36540\\_LDT.zip](http://www.jisoiluminacion.es/Ficheros_LDT/36540_LDT.zip)

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

[http://www.jisoiluminacion.es/Ficheros\\_IES/36540\\_IES.zip](http://www.jisoiluminacion.es/Ficheros_IES/36540_IES.zip)

Este producto contiene una fuente luminosa de la clase de eficiencia energética D.

This product contains a light source of energy efficiency class D.

Ce produit contient une source lumineuse de classe d'efficacité énergétique D.